



DORON BUILDERS AND CONSTRUCTION SUPPLIES LTD. CO.

Lot 8 Blk. 1 Jasmin St., Sampaguita Subd., Camarin, Caloocan City
Tel. No. 962-2881 Telefax 962-2882 email: doronbuilders@yahoo.com

Product Info

DORON-FIL (CORK)

(Non-Extruding Type Concrete Joint Filler)

Comply with: ASTM D-1751-65; AASHTO M-213-65
Federal Specs. HHH-341e, Type 1

DESCRIPTION: Is made from selected granulated cork bonded with hot bituminous asphalt mixture and pre-molded between first class sheets of asphalt saturated felt paper. It is resilient, water and insect resistant and easily handled, it is pneumatic cushion. Its resilience and compressibility enable it to deform under pressure with no extrusion and almost total recovery in the range of 80% to 95% of its original thickness, as the applied pressure is removed.

USAGE: Is used wherever a bituminous fiber-type is required;

1. As a filler strip for all expansion joints in concrete highways and streets.
2. As expansion joint material in all concrete paving work such as driveways, sidewalks, curbs, and gutters.
3. As expansion strips between adjacent constructions: buildings and roadways, manholes, and other insets in concrete paving.

The top of the joint can be sealed with DORON SEAL (Hot poured, Elastomeric type) or DORON SEAL (Cold Applied, non-hardening mastic)

PROCEDURE IN CUTTING: Score with a knife to a depth of 1/4" on both sides. It will break cleanly along the scored line.

LIMITATIONS: Should not be used in conjunction with polysulfide, polyurethane, or other polymer base joint sealants.

SIZES: Lengths: 5 feet to 10 feet
Width: 3 feet
Thickness: 1/4", 1/2", 3/4", 1"

JESUS CHRIST ALONE SAVES