



# DORON BUILDERS AND CONSTRUCTION SUPPLIES LTD. CO.

Lot 8 Blk. 1 Jasmin St., Sampaguita Subd., Camarin, Caloocan City  
Tel. No. 962-2881 Telefax 962-2882 email: doronbuilders@yahoo.com

## Product Info.

### **DORON SEAL CONCRETE JOINT SEALER** (Hot-Poured Elastic Type) ASTM D-1190-64; AASHTO M-173-60

**DESCRIPTION:** Doron Seal Concrete Joint Sealer (Hot-Poured Elastic Type) is an asphaltic plug joint suitable for low to medium movement capacity expansion joints on highway bridges. It is of rubberized asphalt, highly selected drying and non-drying oils carefully engineered to produce a heavy-bodied, self-curing sealant between horizontal joints in concrete and metal. This product maintains good bonding with concrete during expansion and contraction and is waterproof to prevent infiltration of moist, oil, dirt and other foreign substances.

**USAGE:** Doron Seal Concrete Joint Sealer is primarily used for joints of concrete highways, roads, and airfield pavements.

**PREPARATION:** Must be clean and dry. Free from loose materials, efflorescence and foreign matters, by using a wire brush and/or air compressor if desired.

**APPLICATION:** Ensure to completely melt the material at a temperature ranging from 400°F to 450°F before pouring to the joint surface. **NOTE:** Above 450°F is not recommended because it will cause a breakdown of the base and will make the cool product softer and tackier.

**PACKAGING:** Pail: 16 kg. Bag 25 kg.

**JESUS CHRIST ALONE SAVES**